

1-Mark Turn-Key Industrial Computer

More than a home computer

A great addition to the I-Mark dot-peen and scribe marking machines or the CMT Eclipse laser marking machines is the CMT industrial PC. The windows-based PC is a fanless PC with no moving parts. The complete upgrade includes Windows software, I-Mark or CMT Eclipse marking software preloaded, 17" monitor and mount, keyboard and shelf.

Compatible Systems

- I-Mark M and MS Series included
- I-Mark C Series
- CMT Eclipse LE16 Compact
- CMT Eclipse LE24 Round
- CMT Eclipse LE48 Large Bed
- CMT Eclipse LER Rotary Turn Table
- CMT Eclipse Tunnel Automated Conveyor

IMPC - Components

- Monitor 17" and monitor mount*
- Keyboard with integrated mouse. Membrane keyboard for laser systems
- Keyboard shelf*
- Laser or I-Mark software loaded and tested
- All components to be mounted to system or marking machine base
- IMPC Windows 10 (64 bit)
 - Fanless
 - No moving parts
 - Configurable
 - 24VDC quick disconnect
 - This system includes an aluminum heat sink for durability and reliability and is ideal for many production environments.

^{*} Style of mount and shelf varies model to model. Laser mount shown at right.




Marking Machines


IM-PC Key Features


- Bay Trail motherboard
- 1.83GHz Quad Core Ⅷ
- 24VDC power connector

- Aluminum head sink
- Slotted mounting bracket
- Fanless cooling









PC Specifications Star	ndard Model
------------------------	-------------

PC Specifications	C Specifications Standard Model	
Part number	IM-PC	
System I/O	2x Ethernet ports (10/100)	
	1x RS232 port	
	1x RS232/422/485 Port	
	2x USB 3.0 ports	
	1x USB 2.0 port	
	1x VGA port	
	1x HDMI port	
	1x Audio jack 3.5mm	
Storage devices	mSATA SSD 128GB	
СРИ	Bay Trail Quad Core	
CPU speed	1.83GHz Base	
	2.16GHz Turbo (4 Cores, 4 Threads)	
Operating system	Windows 10 (64 bit)	
Memory	8GB	
Power supply	24VDC Power entry M12 4pin	
Power consumption	25 Watts	
Temperature	Operating: 0° to 50°C (32° to 122°F)	
Relative humidity	Non-condensing: 20% to 80%	
Shock	Operating: 10G	
Vibration	Operating: 1G from 57~2000Hz	
Warranty	12 Month limited warranty	
·		